

Radiator Blowout: Motor Scrapers Standard Operating Procedure

REFUSE DISPOSAL DIVISION

Greens Processing

Periodic radiator blowout is essential! By keeping the cooling system free from dust, debris and trash, the operator ensures positive cooling. Benefits include long engine life, improved engine performance, reduced fuel consumption and exhaust emissions.

- 1. Always allow five-minute cool down prior to engine shut-off.
- 2. Ensure you are wearing all safety gear (i.e., glasses, gloves, respirator, dust masks, etc.).
- 3. Machinery park mode all attachments lowered.
- 4. Blowout front engine radiator, back engine radiator and all air cleaners.
- 5. Ensure all air cleaner indicators are in the green.

Benefit of Compliance to Instruction:

- Increased life span of machinery
- Increased productivity
- Reduced fuel consumption

Consequence of Non-Compliance to Instruction:

- Machinery breakdown -> high cost of replacement parts
- Reduced productivity
- Increased emissions
- Disciplinary action

Environmental Management System (EMS) –ISO 14001 PROCESS MAP #: GP-1.0 / CD-1.0

Reviewed by: Gary Gobel, Landfill Superintendent

Approved by: Steven F. Fontana, Deputy Environmental Services Director, Refuse Disposal

The on-line version and secured hardcopy are the controlled documents. The secured hardcopy will be identified by a "Controlled Copy" stamp (in red) and RDD Deputy Director signature. Any other documents are uncontrolled. Verify revision level status on-line or contact the EMR

Radiator Blowout: Scrapers

Effective Date: February 20, 2004

Document Number: RDD-SOP-GP-11, Revision-1